


**DATA  
OUTPUT**

- Non waterproof
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch, ABS/INC, data hold, TOL, set
- Battery LR44, data output
- Made of stainless steel
- Supplied with bracket to be mounted on the back
- Optional accessory: wireless transmitter (code **7315-1150**), data output cable (code **7302-SPC7**, keyboard format), data output cable (code **7305-1150**, serial port format)



(mm)

Code	Range	Accuracy	B	C	D	E	F	L
<b>7102-100</b>	100mm/4"	±0.02mm	4	20	6	24	40	245
<b>7102-150</b>	150mm/6"	±0.03mm	4	20	6	24	40	296
<b>7102-200</b>	200mm/8"	±0.03mm	4	20	6	24	40	345
<b>7102-300</b>	300mm/12"	±0.04mm	4	20	6	24	40	445
<b>7102-400</b>	400mm/16"	±0.05mm	4	20	6	24	40	545
<b>7102-500</b>	500mm/20"	±0.05mm	5.5	24	8	32	45	685
<b>7102-600</b>	600mm/24"	±0.08mm	5.5	24	8	32	45	785
<b>7102-800</b>	800mm/32"	±0.10mm	5.5	24	8	32	45	985
<b>7102-1000</b>	1000mm/40"	±0.10mm	10.5	31	9.5	40	60	1245

## DIGITAL VERTICAL SCALES



**7102-300**

