

PEN-TYPE CONDUCTIVITY TESTER (BASIC TYPE) CODE 0416-EB01

- Suitable for water quality testing, aquaculture, food processing, scientific research, etc.
- Mini design with an electrode diameter of 10mm
- Manual temperature compensation
- With reading stabilization reminder function
- Replaceable electrodes
- Low voltage alarm
- CR2032 battery, automatic power off
- Probe protection level: IP57



SPECIFICATION

SPECIFICATION		
Measuring range	(0~99.9)µS/cm, (100~999)µS/cm, (1.00~9.99) mS/cm, (10.00~99.99)mS/cm, (100~199.9)mS/cm	
Resolution	0.01µS/cm, 0.1µS/cm, 1µS/cm, 0.01mS/cm	
Accuracy	±1.5%FS	
Temperature compensation range	0~99.9°C (manual)	
Calibration mode	1 point (automatic recognition), electrode constant calibration	
Standard solution	1413µS/cm	
Power supply	CR2032 battery	
Dimension (W×D×H)	50×188×17mm	
Weight	60g	

STANDARD DELIVERY

Main unit	1pc
Calibration powder (0416-EB01-S)*	2pcs

^{*}dissolve in distilled water to 50mL

OPTIONAL ACCESSORY

Conductivity electrode	0416-EB01-E