SINGLE GAS DETECTORS



- Detect combustible gas (EX, including CH₄, C₃H₈, H₂, etc), O₂, CO or H₂S by default, support more than 30 types of gas sensors, customization for detecting toxic gases (such as NO, NH₃, PH₂, etc) available
- Adjustable alarm level, alarm mode: sound, light, vibration
- Adjustable calibration level
- Sampling method: natural diffusion
- High concentration protection for sensor
- Up to 500 alarm records storage capacity
- Self-test on startup
- Display with backlight
- Language: English, Chinese
- Low battery indication
- Explosion proof level: Ex ib IIC T4 Gb



calibration cap (included)



0611-SG01

SPECIFICATION

Code	0611-SG01	0611-SG02	0611-SG03	0611-SG04	
Gas	combustible gas/EX	O ₂	CO	H ₂ S	
Range	0-100%LEL	0-30%vol	0-1000ppm	0-100ppm	
Resolution	1%LEL	0.1%vol	1ppm	1ppm	
Accuray	±5%FS	±5%FS			
Response time	T ₉₀ <60s	T₀<60s			
Operation environment	temperature: -10°C~55	temperature: -10°C~55°C; humidity: <95%RH, no condensation			
Sensor lifetime	2 years (depending on	2 years (depending on working environment)			
Power supply	3.7V rechargeable Li-id	3.7V rechargeable Li-ion battery, working time>8h			
Dimension (LxWxH)	124×60×46mm	124×60×46mm			
Weight	205g	205g			

STANDARD DELIVERY

Main unit	1 pc
Calibration cap	1 pc
AC/DC adapter and charging cable	1 pc