





- Red horizontal and vertical cross laser lines
 Self-leveling within ±3°, self-leveling time within 4s, audible and visual warning when out of ±3°
- Folding legs for angle and height adjustment
 Outdoor use with the detector (code: 4917-DETECTOR)



folding legs for angle and height adjustment



application examples



SPECIFICATION

Laser line width	2±0.5mm (within 5m)	
Laser type	630~660nm, class II, <1mW	
Beam angle	120±0.5°	
Self-leveling range	±3°	
Working distance	indoor: 30m, outdoor: 50m with detector (optional)	
Accuracy	0.2mm/m	
Operation temperature	-10~40°C	
Power supply	3×AA batteries, for 3 hours working	
Dimension	100×82×104mm	
Weight	620g	

OUTDOOR DETECTOR (OPTIONAL)

Detecting distance	horizontal 1~50m, vertical 1~30m	
Detecting accuracy *	high accuracy ±1.5mm, low accuracy ±2.5mm	
Power supply	9V battery	
Dimension	168×58×30mm	
Weight	140g (battery included)	

^{*} Use high accuracy detection mode within 15m, use low accuracy detection mode over 15m



stand (included with outdoor detector)



outdoor detector (optional)

STANDARD DELIVERY

•		
Main unit	1 pc	
1/4" to 5/8" tripod adaptor	1 pc	
Battery (AA)	3 pcs	