



# MEASURING TIPS FOR EXTERNAL SCREW THREAD MICROMETERS

**INSIZE PLUS**  
MADE IN EUROPE

- Supplied in pair
- Made of hardened steel
- Suitable for **3680** series micrometers



**7390-T104**



## 60° thread angle

Code	Pitch
<b>7390-T101</b>	0.35-0.5mm/ 72-48TPI
<b>7390-T102</b>	0.6-0.8mm/ 44-32TPI
<b>7390-T103</b>	0.9-1.25mm/ 28-18TPI
<b>7390-T104</b>	1.5-2mm/ 16-11TPI
<b>7390-T105</b>	2.5-3.5mm/ 10-7TPI
<b>7390-T106</b>	4-6mm/ 6-4TPI

## 55° thread angle

Code	Pitch
<b>7390-T201</b>	60-48TPI
<b>7390-T202</b>	40-32TPI
<b>7390-T203</b>	28-22TPI
<b>7390-T204</b>	20-16TPI
<b>7390-T205</b>	14-11TPI
<b>7390-T206</b>	10-7TPI
<b>7390-T207</b>	6-4TPI

## 30° thread angle

Code	Pitch
<b>7390-T301</b>	1.5mm
<b>7390-T302</b>	2mm
<b>7390-T303</b>	3mm
<b>7390-T304</b>	4mm
<b>7390-T305</b>	5-6mm
<b>7390-T306</b>	7-8mm
<b>7390-T307</b>	9-10mm
<b>7390-T308</b>	12-14mm