

## DC POWER SUPPLY



- Four-digit LED display
- Independent voltage and current control knob
- Output switch control
- Panel locking function to prevent misoperation
- OVP/OCP protection
- 3 shortcut keys for presetting

### SPECIFICATION

Code	9913-PS326	9913-PS3210
Rate output voltage	32V	32V
Rate output current	6A	10A
Maximum output power	192W	320W
Voltage	Setting resolution	10mV
	Setting accuracy	$\leq 0.1\% + 10\text{mV}$
	Readback resolution	10mV
	Readback accuracy	$\leq 0.1\% + 10\text{mV}$
	Load regulation	$\leq 0.1\% + 5\text{mV}$
	Line regulation	$\leq 0.01\% + 5\text{mV}$
	Ripple	$\leq 10\text{mVrms}$
Current	Setting resolution	1mA
	Setting accuracy	$\leq 0.2\% + 3\text{mA}$
	Readback resolution	1mA
	Readback accuracy	$\leq 0.2\% + 3\text{mA}$
	Load regulation	$\leq 0.2\% + 3\text{mA}$
	Line regulation	$\leq 0.2\% + 3\text{mA}$
	Ripple	$\leq 5\text{mArms}$
OVP	0~33V	0~33V
OCP	0~7A	0~10.2A
Work condition	temperature: 0°C~40°C, humidity: $\leq 80\%$ RH	
Storage condition	temperature: -20°C~60°C, humidity: $\leq 80\%$ RH	
Cool system	fan cool	
Power supply	110V/220V $\pm 10\%$ , 50Hz/60Hz	
Dimension	230x80x150mm	
Weight	1.47kg	1.96kg

### STANDARD DELIVERY

Main unit	1 pc
Test lead	2 pcs