



VIDEO

- Suitable for epoxy resins and cold mosaic compound of polyester castable
- High efficiency, simple and reliable



cold mounting compound  
(optional)

### SPECIFICATION

|                     |               |
|---------------------|---------------|
| Maximum vacuum      | -58KPa        |
| Vacuum chamber size | Ø260×125mm    |
| Transposition speed | 5r/min        |
| Input power         | 6W            |
| Power supply        | 220/110V      |
| Dimension           | 460×400×403mm |
| Weight              | 30kg          |

### STANDARD DELIVERY

|                     |        |
|---------------------|--------|
| Main unit           | 1 pc   |
| Vacuum pump         | 1 pc   |
| Ø25mm mold          | 1 pc   |
| Ø30mm mold          | 1 pc   |
| Ø40mm mold          | 1 pc   |
| Ø50mm mold          | 1 pc   |
| Epoxy resin (400g)  | 1 pc   |
| Curing agent (200g) | 1 pc   |
| Waxed paper tray    | 10 pcs |

## VACUUM MOUNTING PRESS CODE MLP-MP25



### OPTIONAL ACCESSORY

|                        |                  |
|------------------------|------------------|
| Cold mounting compound | MLP-CM1, MLP-CM6 |
| Epoxy resin            | MLP-CM3, MLP-CM4 |