

## GAUGE MARKING INSTRUMENTS (MARKING POINT)



STM-G1



STM-G4



STM-G2

- According to ISO6892-1
- Suitable for marking tensile specimen of metal bar
- The percentage elongation after fracture of a material can be accurately measured by uniformly distributed markers on the specimen to assess the mechanical property of the material

### SPECIFICATION

Code	STM-G1	STM-G2	STM-G3	STM-G4
Marking method	manual	electric		pneumatic
Spacing of markers	10mm	5/10mm	10mm	5/10mm
Number of markers	30 points	1 point	40 points	1 point
Max. gauge	300mm	300mm	400mm	500mm
Accuracy	±0.1mm	±0.05mm	±0.05mm	±0.05mm
Specificity	multipoint quick and easy	high-accuracy highly efficient easy operation	high-accuracy highly efficient easy operation	high-accuracy highly efficient marking force can be adjusted
Power supply	-	AC 220V, 50Hz		
Dimension (W×D×H)	490×200×300mm	460×315×450mm	710×315×450mm	810×350×520mm
Weight	22kg	25kg	30kg	60kg

### STANDARD DELIVERY

Main unit	1 pc
-----------	------

### OPTIONAL ACCESSORY

Air pump *	STM-G-1
------------	---------

\*For STM-G4