

WIRELESS DATA TRANSFER SYSTEM

APPLICABLE FOR
OTHER BRANDS



Code	Description	Applicable products
7306-2	receiver	USB and RS232 connection ports, strong transmission signal, the maximum distance is 100m
7306-1	mini receiver	USB connection port, for short distance (within 20m) or barrier-free area
7306-20	transmitter	digital calipers, digital depth gages and digital height gages (not for 1103, 1150)
7306-30	transmitter	digital micrometers, digital three point internal micrometers (not for 3631, 3632, 3108, 3109, 3635)
7306-40	transmitter	digital indicators digital protractors



receiver
7306-2



transmitter
7306-20

DATA COLLECTION:

- 1) Single collection: press the read button once to collect the reading from measuring tool once.
- 2) Multi collection: press the read button once to start collecting readings from measuring tools continuously, press the button again to stop collecting. Total collection times and interval time can be adjusted.



measuring tools code A, B, C

	A	B	C	D	E	F	G
1	10.88	A					
2	5.963	B					
3	50.05	C					
4	25.49	D					
5	50.05	C					
6	10.88	A					
7	25.51	D					
8	5.965	B					
9	10.87	A					
10	50.04	C					
11	25.05	D					
12	50.03	C					
13	5.963	B					
14	50.05	C					

- DISPLAY: data can be input to Excel as keyboard signal.

All data are displayed in the same column.
Each measuring tool can be coded such as A, B, C, etc.

- CONNECTION: one receiver can be connected to 30 transmitters.

