

# PEN-TYPE DIGITAL MULTIMETER CODE 9241-ML200

- Auto/manual ranging
- Maximum mode
- Data hold
- Low battery display
- Auto power off
- Safety rating: CAT III 600V



probe (included)



clips (included)

## SPECIFICATION

Function	Range	Resolution	Accuracy
<b>DC Voltage</b>	200mV/2V/20V/200V/600V	0.1mV/1mV/10mV/0.1V/1V	$\pm(0.7\%+2)$
<b>AC Voltage</b>	200mV/2V/20V/200V	0.1mV/1mV/10mV/0.1V	$\pm(0.8\%+3)$
	600V	1V	$\pm(1.0\%+3)$
<b>DC Current</b>	20mA/200mA	10 $\mu$ A/0.1mA	$\pm(1.5\%+3)$
<b>AC Current</b>	20mA/200mA	10 $\mu$ A/0.1mA	$\pm(2.0\%+3)$
<b>Resistance</b>	200 $\Omega$	0.1 $\Omega$	$\pm(1.0\%+3)$
	2k $\Omega$ /20k $\Omega$ /200k $\Omega$ /2M $\Omega$	1 $\Omega$ /10 $\Omega$ /0.1k $\Omega$ /1k $\Omega$	$\pm(1.0\%+1)$
	20M $\Omega$	10k $\Omega$	$\pm(1.0\%+5)$
<b>NCV</b>	>50V AC		
<b>Logic level test</b>	<1.5V (green LED on)		
	1.5~3.5V (green & red LED off)		
	>3.5V (red LED on)		
<b>Diode</b>	open circuit voltage 1.5V		
<b>Continuity buzzer</b>	<60 $\Omega$		
<b>Power supply</b>	2 $\times$ 1.5V AAA batteries		



## STANDARD DELIVERY

Main unit	1 pc
Probe	1 pc
Clip	2 pcs
1.5V battery	2 pcs