

PORTABLE LEEB HARDNESS TESTER CODE ISHL-P200

ATTENTION:
BASIC MODEL

WITH BUILT-IN PRINTER

DATA
OUTPUT



hardness test block D (included)



small support ring (included)



printer paper (optional)



software CD (included)

- Supplied with impact device D and built-in printer
- Based on Leeb (HLD), converted to Vickers(HV), Brinell(HB), Rockwell(HRC and HRB), Shore(HS) and tensile strength(MPa)
- Set test times (1~32) to have average value
- Memory of 100 test values for browsing, print and output
- Low and high limits with judgement
- Automatic power off

SPECIFICATION

Min. reading	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa	
Accuracy	±8HLD (when HLD=760±30)	
Display	Leeb, conversion hardness, material, impact direction, test times, average value, time	
Applicable workpiece	minimum weight	5kg
		2kg (on solid support)
		0.1kg(coupled on plate)
	minimum thickness: 5mm	
	minimum radius of curved surface: 30mm	
	maximum roughness(Ra): 1.6µm	
Power supply	built-in rechargeable battery	
Dimension	198×82×30mm	
Weight	320g	

STANDARD DELIVERY

Main unit with printer	1pc
Impact device D	1pc
Hardness test block D	1pc
Printer paper	1pc
Small support ring	1pc
Cleaning brush	1pc
USB cable and software	1pc
AC/DC adapter	1pc

OPTIONAL ACCESSORY

Couplant	ISH-COUPPLANT
Hardness test block D	ISHL-P100-BLOCK
Printer paper	ISHL-P200-PAPER
Support rings	see details

APPLICABLE MATERIAL AND HARDNESS RANGE FOR IMPACT DEVICE D

Material	HLD	HV	HB	HRC	HRB	HS	Tensile strength(MPa)
Steel & cast steel	300-900	81-955	81-654	20-68	38-100	32-100	375-2639
Tool steel	300-840	80-898		20-67			
Stainless steel	300-800	85-802	85-655		46-101		
Cast iron	360-650		93-334				
Cast aluminum alloy	170-570		19-164		23-84		
Brass	200-550		40-173		13-95		
Bronze	300-700		60-290				
Copper	200-690		45-315				