

# QUALITY INSPECTION TORQUE WRENCH

MEASURE THE TORQUE  
OF TIGHTENED BOLT



IST-4W135A

- Measure the torque of tightened bolt with retightening method, read the torque value when the looseness is detected
- Two measuring modes:
  - M1: automatic detecting mode, for normal bolts
    - retighten the bolt, the torque value is displayed on screen when the wrench automatically detects the looseness, both green and red LED light on and buzzer sounds
  - M2: manual detecting mode, for long bolts
    - retighten the bolt, read the torque value when the looseness is detected by hand
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode (only for M2 measuring mode)
- Clockwise and count-clockwise operation
- Memory of 50 results
- Power off in 15 minutes automatically
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)

## SPECIFICATION

Code	IST-4W30A	IST-4W135A	IST-4W200A	IST-4W340A
Range	6~30N.m	27~135N.m	40~200N.m	68~340N.m
Accuracy	clockwise	±2%		
	counter-clock wise	±3%		
Resolution	0.01N.m	0.1N.m	0.1N.m	0.1N.m
Square driver (L)	1/4"	3/8"	1/2"	1/2"
Power supply	2xAA batteries, for 110 hours working			
Length	390mm	415mm	530mm	650mm
Weight	760g	940g	1340g	1540g

## OPTIONAL ACCESSORY

Calibration cable	IST-W-CABLE
-------------------	-------------