## **DIGITAL TORQUE ADAPTER**





IST-5W135A

- Clockwise and counter-clockwise operation
- Set the desired torque first. After reaching the desired torque, set the angle and turn the wrench at this angle to apply extra torque
- Unit: N.m, in.lb, ft.lb, kg.cm, degree
- Peak and track working mode
- Target torque or angle value can be set, with audible and visible alarm: green LED light on and buzzer sounds when torque or angle value is 80%~100% of target torque or angle both green and red LED light on and buzzer sounds when target torque or angle value is reached
- Power off in 2 minutes automatically
- Memory 50 measurement values for browsing
- With overload record (once the torque reaches 110% of the maximum range)



working with mechanical wrench

## **SPECIFICATION**

Code		IST-5W30A	IST-5W135A	IST-5W200A	IST-5W340A
Range	torque	6 ~ 30N.m	27 ~ 135N.m	40 ~ 200N.m	68 ~ 340N.m
Range	angle 0 ~ 999°				
	clockwise	±3%			
Accuracy	counter-clock wise	±4%			
	angle	±2° (rotate 90°)			
Resolution	torque	0.01N.m	0.1N.m	0.1N.m	0.1N.m
Resolution	angle	1°			
Square driv	er (L)	1/4"	3/8"	1/2"	1/2"
Power suppl	ly	2xAAA batteries			
Length		Ø85×60mm	Ø85×75mm	Ø85×80mm	Ø85×80mm
Weight		150g	220g	240g	240g

## OPTIONAL ACCESSORY

Calibration cable IST-SD-CABLE	Calibration cable
--------------------------------	-------------------

